



## M12 Kabeldosen mit Käfigzugfederanschluss M12 female connectors with cage clamp connection




Binder bietet nun auch konfektionierbare 4- und 5-polige Kabel- und Winkeldosen mit Käfigzugfederanschluss an, die auf Grund der konstanten Federklemmung weitestgehend unempfindlich gegen Vibrationen sind. Die kurze Montagedauer, sowie der gleichbleibende Druck vom Leiter auf den Kontakt gehören zu den Stärken der Steckverbinder.

Binder now offers field wire able 4 and 5 pole straight and angled female cable connectors with cage clamp connection. Due to the constant spring pressure these connectors are mostly resistant to vibrations. Short installation time as well as persistent pressure of the conductor to the contact is amongst the strengths of these connectors.

Polzahl	Contacts	4, 5
Strom	Rated current	4 A
Bemessungsspannung	Rated voltage	125 V - 250 V
Schutzart	Degree of protection	IP 67
Kontaktoberfläche	Contact plating	Au
Anschluss	Termination	Käfigzug/cage clamp



## M12 Kabeldosen mit Käfigzugfederanschluss M12 female connectors with cage clamp connection



Polzahl Contacts	Kabeldurchlass Cable outlet	Bestell-Nr. Ordering-Nr.	Polzahl Contacts	Kabeldurchlass Cable outlet	Bestell-Nr. Ordering-Nr.	Polzahl Contacts	Kabeldurchlass Cable outlet	Bestell-Nr. Ordering-Nr.	Kodierung Coding	Serie Series
4	4-6 mm	99-0524-14-04	4	4-6 mm	99-0524-24-04	4	4-6 mm	99-1526-814-04	A	713
	6-8 mm	99-0524-12-04		6-8 mm	99-0524-52-04		6-8 mm	99-1526-812-04		
5	4-6 mm	99-0536-14-05	5	4-6 mm	99-0536-24-05	5	4-6 mm	99-1538-814-05	A	713
	6-8 mm	99-0536-12-05		6-8 mm	99-0536-52-05		6-8 mm	99-1538-812-05		
4	-	-	4	-	-	5	6-8 mm	99-1536-810-05	B	715
5	-	-	5	-	-	5	6,5-8,5 mm	99-1536-910-05		
4	-	-	4	-	-	4	6-8 mm	99-3726-810-04	D	825